

low thermal expansion prepregs prepn e.g. for PCB's - by filling inorganic particles into monofilament strand, impregnated resin varnish and drying

Patent Assignee: MATSUSHITA ELECTRIC WORKS LTD (MATW)

Number of Countries: 001 Number of Patents: 001

Patent Family:

Patent No	Kind	Date	Applicat No	Kind	Date	Week
JP 9003217	A	19970107	JP 95151850	A	19950619	199711 B

Priority Applications (No Type Date): JP 95151850 A 19950619

Patent Details:

Patent No	Kind	Lan Pg	Main IPC	Filing Notes
JP 9003217	A	8	C08J-005/24	

Abstract (Basic): JP 9003217 A

Prepn. of reinforcing material (A) comprises filling 1-30 pts.wt. inorganic particles (A1) with average particle size 1,000 nm or less into 100 pts. wt. of strand (A2) composed of monofilaments. (2) impregnating resin varnish (B) into (A) under 1-300 Torr, and (3) drying.

USE - (I) is useful as material for prepn. of composite materials e.g. PC substd.

ADVANTAGE - (I) gives composite materials having small coefficient of thermal expansion and good soldering resistance.

Dwg.0/1

Title Terms: LOW; THERMAL; EXPAND; PREPREG; PREPARATION; PCB; FILL; INORGANIC; PARTICLE; MONOFILAMENT; STRAND; IMPREGNATE; RESIN; VARNISH; DRY

Derwent Class: A85; L03; V04; X12

International Patent Class (Main): C08J-005/24

International Patent Class (Additional): B29B-011/16; B29B-015/14; B29K-105-06; C08J-005/10

File Segment: CPI; EPI

?